

Pallet Truck

GP-EP

The GP-EP series electric pallet truck is professional solution for load handling in warehouse and stores. The Truck is designed and manufactured according to the latest technology and components to ensure excellent performance. It is the best choice when it comes to price efficient material handling equipment. It can be widely used in factory, warehouse, medical, super market for material handling. The truck is supplied with battery power indicator, key switch and emergency off button. Confirms to the DIN EN 1726-1 requirements. Its Compact design with heavy-duty loading capacity of 2000kg and 2500kg, easy to move in the most confined spaces and narrow aisles such as retail stores, small warehouses and factories.



Technical Specifications

Model Specs	Model	Unit	GP-EP15	GP-EP15A1	GP-EP20A1	GP-EP25A1	GP-EP30A1	
Feature	Load capacity	Q(kg)	1500	1500	2000	2500	3000	
	Load center	C(mm)	600					
	Wheel base	Y(mm)	1284/1345	1234	1493			
	Operating type		Drive		Drive/Stand On			
Dimension	Min.fork lowered height	H1(mm)	85					
	Max.fork lifting height	H(mm)	195				205	
	Max.lifting height	H2(mm)	110				120	
	Fork size(length/width/thickness)	LxWxT(mm)	1150(1200)/160/44		1150(1200)/185/55			
	Min.Turning radius	Wa(mm)	1510	1400	1746/2158			
	Min.Aisle width for pallets 800×1200,Pedal fold/unfold	Ast(mm)	1960	1850	2175/2585			
	Min.Aisle width for pallets 1000×1200,Pedal fold/unfold	Ast(mm)	1960	1850	2175/2585			
	Overall length	L1(mm)	1626	1630	1916/2333			
	Overall width	B(mm)	560/685	724	790			
	overall height(with handle/without handle)	H4(mm)	1190/710	685/1220	1455/845			
Outside with between legs	B1(mm)	560/685	540/600/685	550/600/685				
Wheels	Wheel type		PU					
	Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/0/4	1/2/4				
	Driving wheel	mm	φ252×67		φ248×75			
	Balance wheel	mm	-	φ99.5×40	φ115×55			
	Bearing wheel	mm	φ80×58(Double wheel)		φ80×80(Double wheel)			
Electrical configuration	Brake		Electromagnetic/Regenerative					
	Drive motor/Lift motor/Steering motor	kw	DC0.63/DC0.8/0		AC1.5/DC2.0/DC0.15			
	Battery voltage	V	24					
	Battery capacity	Ah	70		240			
	Controller		CURTIS					
Weight	Battery weight	kg	48		252			
	Service weight with battery	kg	275	285	840			

* GlobePharos retains the right to adjust the specification and configurations to improve the performance without notice, please contact us to get the newest information.