

**GLOBEPHAROS**



**GP50-70**

**Diesel Forklift**

**CE**  
CE CERTIFICATE

**MAIN SPECIFICATIONS**

General	1	Model		GP50-JF	GP60-JF	GP70-JF
	2	Power Type		Diesel		
	3	Rated Load Capacity	Q(kg)	5000	6000	7000
	4	Load Centre	C(mm)	600		
Characteristic & Dimension	5	Rated Lift Height	H3(mm)	3000		
	6	Free Lift Height	H2(mm)	152		
	7	Fork Size (L×W×T)	mm	1220×150×60		1220×150×65
	8	Mast Tilt Angle (F/R, α°/β°)	deg	6°/12°		
	9	Fork Overhang (Wheel Center to Fork Face)	X1(mm)	585		
	10	Rear Overhang	X2(mm)	640	720	
	11	Ground Clearance (Bottom of Mast)	H7(mm)	200		
	12	Length to Face of Fork (Without Fork)	L1(mm)	3510	3590	
	13	Overall Width	B1(mm)	1995		
	14	Mast Lowered Height	H1(mm)	2515	2615	
	15	Mast Extended Height (With Backrest)	H4(mm)	4437		
	16	Overhead Guard Height	H5(mm)	2415		
	17	Turning Radius (Outside)	Wa(mm)	3280	3360	
	18	Min.Aisle width for pallets	Ast(mm)	5285	5365	
Performance	19	Tyre (Front x 4)	mm	8.25-15-14PR		
	20	Tyre (Rear x 2)	mm	8.25-15-14PR		
	21	Travel Speed (No Load)	km/h	20		
	22	Lifting Speed (Full Load)	mm/sec	500	460	
	23	Max.Gradeability (Full Load)	%	35	32	29
	24	Wheelbase	Y(mm)	2250		
Weight	25	Total Weight	kg	7980	8640	9350
	26	Front Axle Weight Distribution (Full Load/No Load)	kg	11660/4010	13050/3880	14570/3860
	27	Rear Axle Weight Distribution (Full Load/No Load)	kg	1320/3970	1590/4760	1780/5490
Power & Transmission	28	Battery	V/Ah	12/90 x 2		
	29	Engine Model		A-6BG1QC		
	30	Engine Manufacturer		ISUZU		
	31	Rated Output / r.p.m.	kw	82.3/2000		
	32	Transmission Type		Automatic Hydraulic		
	33	Transmission Stage (FWD/RVS)		2/2		
	34	Operating Pressure (For Attachments)	Mpa	17		

